

FACADE PASTE FP 75

SEALABLE

pioneers in profiles

APPLICATION RANGE

- Bonding of rubber articles to each other or to concrete parts
- Filling of cavities during repair work

WORK PREPARATION

Ensure that the sealing surfaces are dry, clean, and free of dust and grease. Degrease the adhesion surfaces carefully with Cleaner for G 3000 plus. Remove any corrosive patches.

PROCESSING

The sealing paste is supplied in 600 ml foil tubes. Cut the tube open at one end and place it in a corresponding manual or hydraulic gun. Cut off the tip of the nozzle at an angle of 45° and in a length of 10 to 15 mm, resulting in an outer nozzle diameter of approx. 8 mm. The Cleaner for G 3000 plus is used to clean the tools.

Processing temperature: +5 °C until +35 °C

Curing time: 12 hours to several days depending on weather, layer thickness and surface porosity.

SHELF AND PROCESSING LIFE

Store the unopened tubes at +5 °C to +25 °C for no longer than 12 months. **Please heed the manufacturing date/use before date stated on the tubes.**

Package size: 36 cm x 20 cm x 17 cm

Package weight: 9,6 kg

Stackable: max. 4 cartons



COMPOSITION

The Facade Paste FP 75 made of synthetic rubber and resin has high viscosity levels thanks to the addition of minimum quantities of organic halogen-free solvents.

SAFETY

When handling our products, please comply with the instructions on our EC Safety Data Sheets and the safety warnings provided on our tube labels. Special attention should be paid to the requirements of the Ordinance on Hazardous Substances and the accident prevention regulations issued by the Employer's Liability Insurance Association.

TECHNICAL DATA

BASIS	styrene rubber, contains solvents
COLOUR	black
DENSITY	approx. 1,20 g/cm ³
VISCOSITY	approx. 1,10 mPa.s
SOLID MATTER	approx. 78 %
CONSUMPTION RATE DEPENDING ON SURFACE	approx. 200 - 300 g/m ²

DELIVERY FORM

WEIGHT PER FOIL TUBE	756 g
PACKAGING UNIT	12 tubes per box 60 boxes per pallet



SEALABLE Solutions GmbH
Eisenacher Landstraße 70
99880 Waltershausen
Germany

Phone +49 3622 633-200
Fax +49 3622 633-411
info@seal-able.com
www.seal-able.com

Contact Application Engineer
Mark Fischer
Mobil +49 151 1464 8844
mark.fischer@seal-able.com